

100% ACRYLIC EMULSION PAINT EXTERIOR WALL PAINT



Product Description

INDO-Z 100% Acrylic Exterior Paint is a smooth water based, modified acrylic exterior wall paint.

Technical Details

Areas of application	Cement plasters, brick wall, cement concrete, exterior ceiling, asbestos sheet etc.
Form	Liquid
Thinning Medium	Fresh non saline clean potable water
Thinning Ratio	45% by volume i.e 450 ml of water to 1 Ltr of paint
Stability of thinned paint	To be used within 24 hours
Application Method	Brush, Roller or Spray.
Drying Time	Surface dry time 30 minutes
Recoating Time	4 - 6 hours
Flash Point	N.A. Non-Flammable.
Finish	Smooth with a soft sheen
Coverage	55-60 Sq.ft. / Ltr / 2 coats * *Actual coverage may vary depending on the method & condition of application, surface condition, roughness, porosity and shade

Available Packs

01Ltr 04Ltr 10Ltr 20Ltr

Features



**SMOOTH
SOFT SHEEN**



**WEATHER
GUARD**



**NO CHALK, CRACK
OR PEEL OFF**



**FUNGUS
RESISTANCE**



**EXCELLENT
ADHESION**



**WATER
REPELLENCY**



**ECO
FRIENDLY**



**UV
PROTECTION**

How to Apply

Pre – Painting Surface Preparation

- ▶ Proper preparation of surface is the key to a professional and long lasting finish. All possible sources of moisture & dampness must be checked & repaired. Leakages must be repaired and stopped completely.
- ▶ Scrap the surface thoroughly to remove loose or flaking material, old paint, dust, grease and dirt.
- ▶ The surface should be free from fungus, algae growth and moisture.
- ▶ Treat the infected surface with a liberal coat of fungicidal solution.
- ▶ Surface imperfection like dents, cracks, holes are to be filled using Indocem's Crack filler or mixture of white cement and clean fine sand in the ratio of 1:3.

Paint Application Process

- ▶ Apply a liberal coat of Indocem paints INDOPRIME XS Exterior Wall Primer using the recommended method. Allow to dry for 6 hours, before recoating.
- ▶ Apply 2 coats of INDO Z. An interval of 6 hours between coats should be kept.
- ▶ Additional coats may be necessary for deeper dissemination.
- ▶ For horizontal surfaces, application of 3 coats is recommended.

Post Application Instructions

- ▶ For best performance and result of the paint, ensure proper cleaning & washing of fungal growth at regular intervals of six months.

Precautions & Safety Measures

- ▶ Fresh plaster should be properly cured with plenty of water, for minimum 5 to 6 weeks before application of paint.
- ▶ Anti fungal treatment is recommended for better result.
- ▶ The product should not be applied on surfaces / substrates that are subjected to continuous seepage & dampness.
- ▶ Stir well & strain before use.
- ▶ Do not over thin the paint and over extend the brush.
- ▶ Do not keep or use water-mixed material beyond 24 hours.
- ▶ Do not apply during wet or frosty weather.
- ▶ Primer coat or only topcoat should not be kept exposed during monsoon.
- ▶ Do not breathe vapour of the paint at the time of brush/spray painting. Wear a suitable mask.
- ▶ In case of contact with eyes, rinse immediately with plenty of water. Consult a physician.
- ▶ Keep out of reach of children and away from food, drink and animal feed etc.
- ▶ Containers should be tightly closed after each use. Store in a cool & dry place.
- ▶ Do not pour leftover paint down the drains, dispose off safely.

Shelf Life : 3 years from date of manufacture in original tightly closed containers kept away from direct sunlight & excessive heat.

Information in this sheet is given in good faith, but without warranty as conditions of storage and use vary and are beyond our control.