



WATERPROOF COATING

Product Description

Indocem Paints Alma is a fiber reinforced acrylic polymer liquid applied waterproofing coat. Upon curing, it forms a thick durable film offering excellent waterproofing.

Product Features & Benefits

- ▶ Excellent water proofing protection
- ▶ Crack bridging ability – bridges hairline cracks.
- ▶ Fiber reinforced – Abrasion resistance
- ▶ Surface heat reduction
- ▶ Easy to apply.

Recommended Usage

- ▶ Terraces
- ▶ Parapet Walls
- ▶ Sun Shades
- ▶ Exterior Vertical Walls

Technical Details

| | |
|--------------------|--|
| Form | Viscous Liquid |
| Thinning Medium | Clean potable water. |
| Application Method | Brush, roller. |
| Drying time | Touch dry 4 – 6 hours. |
| Recoating time | 6 hours |
| Finish | Excellent sheen, brilliant white. |
| Coverage | 10 sq.ft / ltr on terraces * 20– 25 sq.ft / ltr/ coat on vertical walls |

*Forced coverage as per the recommended application system.

How to Apply

Pre Painting Surface Preparation

- ▶ New masonry surfaces must be properly and completely cured.
- ▶ Surface should be free from any loose paint, dust or grease. Remove all existing coatings completely.
- ▶ All cracks on the surface, at corner joints and parapets should be properly repaired with suitable crack filler. Any other structural defects should be repaired as per standard construction practices.
- ▶ Intermittent dripping of water and water ponds on the surface, if any, must be repaired properly.

Application Process

Horizontal Surface

- ▶ Apply a self priming coat of ALMA by diluting with 30% clean potable water (3:1) Adhere to the forced coverage requirement. Allow to dry for 6 hours.
- ▶ Apply the first water proofing coat of ALMA without dilution, ensuring the forced coverage requirement, of 25 square foot/Ltr/coat.Allow to dry hard before recoating.
- ▶ Apply the second coat of ALMA as per first coat.
- ▶ For best results, apply parapet-to-parapet to envelope the entire building.

Vertical Surface

- ▶ Apply a self priming coat of ALMA by diluting with 30% clean potable water. Allow to dry for 6 hours.
- ▶ Apply the first water proof coating of ALMA without dilution. Allow to dry.
- ▶ Apply two coats of ALL OUT High Performance Exterior Emulsion Paint or INDO – Z 100% Acrylic Exterior Paint by diluting with 40% water. Allow 6 hours between the coats.

Precautions & Safety Measures

- ▶ Do not apply during rain or extreme temperature.
- ▶ Do not over thin the paint and over extend the brush.
- ▶ Avoid excessive surface abuse which may lead to puncturing of the coating film.
- ▶ Keep out of reach of children and away from eatables.
- ▶ In case of contact with eyes and skin wash immediately with soap and plenty of water. Seek medical advice immediately.
- ▶ Do not pour left over paint down the drain or in water courses.

Post Painting Care :

For the best performance of the product, ensure proper washing and cleaning of all algal and fungal growth, at regular intervals.

Available Packs

01Ltr 04Ltr 10Ltr 20Ltr

Shelf Life: 12 months from date of manufacture in original tightly closed container kept away from direct sunlight & excessive heat.

Information in this leaflet is given in good faith, but without warranty, as conditions of storage and use vary and are beyond our control.

*Conditions apply